




















Technical Data

 **Design**flooring

	Standard	Result
 Size	Planks	1219mm x 178mm
 Thickness	EN 428	3.0mm
 Wear layer	EN 429	0.55mm
K Guard+ (PU) surface protection		Yes
Guarantee	Commercial Domestic	10 Years 15 Years
 Bevelled edge		No
 Type of floorcovering	EN 649	Heterogeneous PVC
 Classification	EN 685	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
 Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	B _{s1} -S1 ≥8kw/m ² Pass
 Slip resistance	EN 13893 BS 7976 DIN 51130	DS Dry 61 Wet 33 R9
 Staining resistance	EN 423	Class 0
 Light fastness	ISO 105-B02	≥ 7
 Abrasion resistance	EN 660-2	Group T
 Dimensional stability	EN 434	≤ 0.25%
 Acoustic impact noise reduction	EN ISO 717-2 EN ISO 140-8	ΔL _w = 4 db
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433	≤ 0.1mm
 Castor chair continuous use	EN 425	Pass
 Thermal conductivity	ISO 8302	0.0147m ² K/W Suitable for underfloor heating. Max 27°C.
 Recycling	Suitable	100%



For more information:

Call: 00 800 777 33 222

Email: info@designflooring.com

Visit: www.designflooring.com

Your space. Your needs. Your style.